



EXPLOSION-PROOF AND FLAMEPROOF

AUDIBLE AND VISUAL SIGNALING DEVICES



2645 Federal Signal Drive
University Park, IL 60484

708-534-4756

signalsupport@fedsig.com

www.fedsig.com



Go beyond this brochure.


Scan to explore more of what
Federal Signal offers on our website.

To learn more, contact your local Federal Signal sales representative.
All trademarks are properties of Federal Signal Corporation.

© 2026 Federal Signal Corporation. S202 | 0426



VISUAL SIGNALS



Visual signals are crucial for alerting, warning, and communicating important messages in industrial settings to ensure safety and efficiency. Federal Signal offers a wide range of industrial visual signals designed to meet the diverse needs of different industries.



EXPLOSION-PROOF LIGHTS

	24XST	27XST	27XL	121X
FEATURES	SUPERVISED HEARING IMPAIRED LOW IN-RUSH	SUPERVISED LOW IN-RUSH	LOW IN-RUSH	
VOLTAGE	24 Vdc	24 Vdc, 120 Vac, 240 Vac	24 Vac/dc, 120-240 Vac	24 Vdc, 120 Vac
LIGHT SOURCE	Strobe	Strobe	LED	LED
LIGHT PATTERN	60 FPM, 65-75 FPM	80 FPM	60 FPM, Steady	60 RPM
LENS COLORS	● ● ● ● ● ●	● ● ● ● ● ●	● ● ● ● ● ●	● ● ● ● ● ●
MOUNTING TYPE	3/4-inch NPT pendant, ceiling and wall mount options (required, sold separately)	3/4-inch NPT pendant, ceiling and wall mount options (required, sold separately)	3/4-inch NPT pendant, ceiling and wall mount options (required, sold separately)	3/4-inch NPT pendant, ceiling and wall mount options (required, sold separately)
NEMA/IP RATINGS	Type 4X, IP66, IP69K	Type 4X, IP66, IP69K	Type 4X, IP66, IP69K	Type 4X, IP66, IP69K
NEC AND ZONE RATINGS	CI D1, CI D2, CII D1, CIII	CI D1, CI D2, CII D1, CIII	CI D1, CI D2, CII D1, CIII	CI D1, CII D1, CIII
AGENCIES	UL/cUL, UL/ULC Fire, CSFM, Marine	UL/cUL, CSFM, Marine	UL/cUL, Marine	UL/cUL, Marine

Note: Certifications and features are SKU specific. Please reference webpages and data sheets for more information.


AUDIBLE SIGNALS

SELECTONE®



UTM

Plug-in
32-tone module



TM33-SD

Custom tone module

Tone modules are sold separately



SELECTONE EXPLOSION-PROOF AMPLIFIED SPEAKERS



EXPLOSION-PROOF AMPLIFIED SPEAKERS

	300X	302X	304X	314X	ASHX	ASUX
VOLTAGE	24 Vac/dc, 120-240 Vac	24 Vac/dc, 120-240 Vac	24 Vdc	24 Vdc	24 Vdc	24 Vdc
POWER	15 W	30 W	15 W	30 W	15 W	30 W
FREQUENCY	0-110	0-114	0-108	0-112	110	114
REQUIRES TONE MODULE	Requires tone module	Requires tone module	Requires tone module	Requires tone module	Requires tone module	Requires tone module
SURFACE MOUNTING	Surface	Surface	Surface	Surface	Surface	Surface
RATINGS	Type 4X, IP66	Type 4X, IP66	Type 4X, IP66	Type 4X, IP66	Type 4X, IP66	Type 4X, IP66
NEC AND ZONE RATINGS	CI D1, CI D2, CII D2	CI D1, CI D2, CII D2	CI D1, CI D2, CII D2, CIII	CI D1, CI D2, CII D2, CIII	CI D1, CI D2, CII D2, CIII	CI D1, CI D2, CII D2, CIII
AGENCIES	UL/cUL, CSFM	UL/cUL, CSFM	UL/cUL, UL/ULC Fire, CSFM	UL/cUL, UL/ULC Fire, CSFM	UL/cUL, UL Fire, CSFM	UL/cUL, UL Fire, CSFM

Note: Certifications and features are SKU specific. Please reference webpages and data sheets for more information.

* With Audio Connector Kits, sold separately, SelectTone powered loudspeakers interface to external 1 V, 2.8 V, 10 V, 25 V, and 70 V audio sources. Reference SelectTone Connector Kits or web pages for more information.

