



FEDERAL SIGNAL

Visual & Audible Signaling Solutions

DATA CENTERS



A B C G R

SLM100 Streamline Modular Multifunctional LED Beacon

- Three separate inputs: steady, flashing and rotating
- PLC compatible with PNP or NPN connections (Except Dock Base, only NPN)
- Seven mounting base options
- Compatible with 12-24VAC/DC or 120-240VAC (Voltage is dependent on selected base sold separately)
- Type 4X, IP66 enclosure, IP69K



A B C G R

RSL Radiant Stack Light

- Available in 12-24VAC/DC or 120-240VAC
- Modular stack light allows up to 7 light modules; 6 light modules + 1 sound module (1 channel); or 5 light modules + 1 sound module (2 channels)
- Type 3R, IP65 enclosure



A B C G R

SLM500 Streamline Modular Multifunctional Combination Audible/Visual Signal

- 3 Channels included
 - Visual signal only
 - Visual signal + tone 1
 - Visual signal + tone 2
- Three flash patterns: 3x strobe (default), fade and steady
- Volume is adjustable between 76-95 dBa @ 10' (86-105 dBa @ 1M) at three output levels (high, medium, low) through an integrated button
- Seven mounting base options
- Compatible with 12-24VAC/DC or 120-240VAC (Voltage is dependent on selected base sold separately)



A B C G R

AV1-LED Flashing Combination Audible/Visual Signal

- Available in 24VDC and 120VAC
- Intermittent or steady light effect
- Surface, integrated 1/2-inch NPT pipe, and 4-inch electrical box mount
- Internal buzzer produces 85 dBa @ 10' (95 dBa @ 1M)
- PLC compatible
- Type 3R enclosure
- Compatible with wall mounting kits LWMB2 (3R applications) and LSWB (4X applications) and corner mount kit LCMB2 (3R applications)



LWMB2

LWMB

LCMB2